

Series	Major uses	Rated voltage range	Rated Capacitance range (μF)	Category temperature range (°C)	Page
TACE	High frequency use, metallized polypropylene film. Permissible large current and anti-vibration	250 to 1000 V _{dc}	0.47 to 22	-40 to +105	113
TACD	High frequency use, metallized polypropylene film. Standard type (Downsizing of TACB series)	250 to 1000 V _{dc}	0.033 to 22	-40 to +105	114
TACC	High frequency use, metallized polypropylene film. Large capacitance type of TACB series	450 to 1000 V _{dc}	1.0 to 18	-40 to +105	117
TACB	High frequency use, metallized polypropylene film.	250 to 800 V _{dc}	0.033 to 22	-40 to +105	118
HACE	High frequency use, metallized polypropylene film. High voltage type and anti-vibration	630 to 2000 V _{dc}	0.18 to 1.5	-40 to +105	121
HACD	High frequency use, metallized polypropylene film. High voltage type of TACD series (Downsizing of HACB series)	630 to 4000 V _{dc}	0.0033 to 1.5	-40 to +105	122
HACB	High frequency use, metallized polypropylene film. High voltage type of TACB series	630 to 4000 V _{dc}	0.001 to 1.2	-40 to +105	125

◆Metallized polypropylene film capacitors

